

# HIGH TIP BUCKET



## FEATURES & BENEFITS

- Hydraulic operated
- Increased dump height (+ 60 cm / 24 in)
- Excellent volume

High tip bucket is the right choice when you need to reach higher and longer. The bucket is equipped with two hydraulic cylinders that push and tip the bucket over its front edge, which gives considerably more tipping height than with a normal bucket. Increase the dump height of the machine by almost 60 cm (24 in) using the high tip bucket. This increased reach enables loading high-side trucks without the need of a ramp. The bucket is an ideal tool for snow removal, loading of wood chips and for loading works on recycling plants etc. The bucket is available with a flat cutting edge.



Model	Volume*	Width	Length	Height	Weight	Code
100	210 l (8.1 ft <sup>3</sup> )	100 cm (39.4 in)	86 cm (33.8 in)	61 cm (24 in)	154 kg (339 lbs)	<b>C890090</b>
130	280 l (9.9 ft <sup>3</sup> )	130 cm (51.2 in)	86 cm (33.8 in)	61 cm (24 in)	174 kg (384 lbs)	<b>C890092</b>
150	320 l (11.3 ft <sup>3</sup> )	150 cm (59 in)	86 cm (33.8 in)	61 cm (24 in)	188 kg (414 lbs)	<b>C890093</b>
180	380 l (13.4 ft <sup>3</sup> )	180 cm (71 in)	86 cm (33.8 in)	61 cm (24 in)	208 kg (460 lbs)	<b>C890094</b>

(\*): verify the lifting capacity of the machine

Compatibility	1.1	2.3	4.2	5.2	5.3 7.2	6.3	7.3	8.4	8.5 9.5	9.6	10 11	6.3SD	7.3SD 8.4SD	9.5SD	12.4*	EZ
Model																
100																
130																
150																
180																

(\*): C890025 adapter required

Very compatible
  Compatible
  Not compatible

