

# JIB CRANE, ONE-PIECE OR TELESCOPIC



## FEATURES & BENEFITS

- Useful for great outreach and high lift
- Safety hook included
- Compact for good visibility
- Versatile lifting attachment for various load handling jobs

The MultiOne Jib Crane provides additional reach for lifting operations. The jib crane is available in either a one piece design or a hydraulically adjustable telescopic design. Each of these designs includes a heavy duty safety hook.

The one-piece jib crane is equipped with two connecting points, one at the tip of the boom and one 500 mm lower.

The telescopic jib crane enables the load to be kept close to the machine and then extended outwards for placement. The steplessly extending and retracting boom allows lifting to places that would otherwise be very hard to reach. Compact design with telescoping cylinder inside the boom and durable wear pads on the outer boom, makes work safe and easy.

The maximum lifting load varies according to the machine on which it is installed.



Model	Length	Structural capacity*	Weight	Code
One-piece	250 cm (98.4 in)	200 kg (440 lbs)	41 kg (90.4 lbs)	<b>C890710</b>
Telescopic	110+60 cm (43.3+23.6 in)	500 kg (1100 lbs)	85 kg (187.4 lbs)	<b>C890712</b>

(\*) verify the lifting capacity of the machine

Compatibility	1.1	2.3	4.2	5.2	5.3 7.2	6.3	7.3	8.4	8.5 9.5	9.6	10 11	6.3SD	7.3SD 8.4SD	9.5SD	12.4*	EZ
Model																
One-piece																
Telescopic																

(\*) C890025 adapter required

Very compatible
  Compatible
  Not compatible

