

AUGER

<http://tiny.cc/auger>



FEATURES & BENEFITS

- Wide range of auger drive units with different torques enables efficient use of 10 cm (4 in) to 100 cm (40 in) augers
- Augers with tungsten teeth available

The powerful hydraulic auger drive unit, combined with various auger diameters, provide excellent flexibility in all soil types.

The auger is the ideal accessory to perform holes for fences, poles for vineyards, for trees planting, for the installation of pillars or streetlights in all types of terrain. The auger drive is available in three versions:

- T1 for normal soil conditions
- T2 for hard, rocky ground, used with augers up to 50 cm (20 in)
- T3 for hard, rocky ground, used with augers up to 100 cm (40 in)

A large variety of augers are also available with replaceable tungsten teeth for the most difficult terrains, and it is also possible to install extensions, each 1 m long, to reach greater digging depths. The augers are equipped with a special joint that allows to make a perfect vertical hole no matter how the machine is positioned. The auger combined with the high hydraulic flow of MultiOne machines allows to drill holes quickly in any terrain.



Model	Torque	Drills	Weight	Code
T1 – standard drive unit	100 kgm	10 - 50 cm (4 - 19.7 in)	90 kg (198 lbs)	C890830
T2 – heavy duty drive unit	180 kgm	10 - 50 cm (4 - 19.7 in)	110 kg (242 lbs)	C890831
T3 – heavy duty drive unit	400 kgm	30 - 100 cm (11.8 - 39.4 in)	150 kg (331 lbs)	C890832

Compatibility	1.1	2.3	4.2	5.2	5.3	6.3	7.2	8.4	8.5	11.6	11.9	EZ5	EZ7 EZ8
Model													
T1													
T2													
T3													

Very compatible
 Compatible
 Not compatible



OPTIONS FOR AUGER

Heavy Duty Auger Drill	Diameter	Length	Code
10	10 cm (4 in)	100 cm (39.4 in)	C890840
15	15 cm (6 in)	100 cm (39.4 in)	C890841
20	20 cm (7.9 in)	100 cm (39.4 in)	C890842
25	25 cm (9.8 in)	100 cm (39.4 in)	C890843
30	30 cm (11.8 in)	100 cm (39.4 in)	C890844
35	35 cm (13.8 in)	100 cm (39.4 in)	C890845
40	40 cm (15.7 in)	100 cm (39.4 in)	C890846
50	50 cm (19.7 in)	100 cm (39.4 in)	C890847
60 - T3 auger only	60 cm (23.6 in)	100 cm (39.4 in)	C890849
70 - T3 auger only	70 cm (27.6 in)	100 cm (39.4 in)	C890851
80 - T3 auger only	80 cm (31.5 in)	100 cm (39.4 in)	C890853
90 - T3 auger only	90 cm (35.4 in)	100 cm (39.4 in)	C890855
100 - T3 auger only	100 cm (39.4 in)	100 cm (39.4 in)	C890857
Auger Drill w/tungsten teeth Rock Drill	Diameter	Length	Code
15	15 cm (6 in)	100 cm (39.4 in)	C890880
20	20 cm (7.9 in)	100 cm (39.4 in)	C890881
25	25 cm (9.8 in)	100 cm (39.4 in)	C890882
30	30 cm (11.8 in)	100 cm (39.4 in)	C890883
35	35 cm (13.8 in)	100 cm (39.4 in)	C890884
40	40 cm (15.7 in)	100 cm (39.4 in)	C890885
50	50 cm (19.7 in)	100 cm (39.4 in)	C890886
60 - T3 auger only	60 cm (23.6 in)	100 cm (39.4 in)	C890888
70 - T3 auger only	70 cm (27.6 in)	100 cm (39.4 in)	C890890
80 - T3 auger only	80 cm (31.5 in)	100 cm (39.4 in)	C890892
90 - T3 auger only	90 cm (35.4 in)	100 cm (39.4 in)	C890894
100 - T3 auger only	100 cm (39.4 in)	100 cm (39.4 in)	C890896
Auger Drill Extension	Diameter	Length	Code
10	10 cm (4 in)	100 cm (39.4 in)	C890860
15	15 cm (6 in)	100 cm (39.4 in)	C890861
20	20 cm (7.9 in)	100 cm (39.4 in)	C890862
25	25 cm (9.8 in)	100 cm (39.4 in)	C890863
30	30 cm (11.8 in)	100 cm (39.4 in)	C890864
35	35 cm (13.8 in)	100 cm (39.4 in)	C890865
40	40 cm (15.7 in)	100 cm (39.4 in)	C890866
50	50 cm (19.7 in)	100 cm (39.4 in)	C890867
60 - T3 auger only	60 cm (23.6 in)	100 cm (39.4 in)	C890869
70 - T3 auger only	70 cm (27.6 in)	100 cm (39.4 in)	C890871
80 - T3 auger only	80 cm (31.5 in)	100 cm (39.4 in)	C890873
90 - T3 auger only	90 cm (35.4 in)	100 cm (39.4 in)	C890875
100 - T3 auger only	100 cm (39.4 in)	100 cm (39.4 in)	C890877