

# ALUMINIUM RAMPS




## FEATURES & BENEFITS

### • Light and Durable

The sturdy aluminium ramps are durable and lightweight for easy handling. These ramps are designed with deep ridge treads for better traction that enables safe and efficient loading and unloading of the MultiOne from trucks and trailers.

**NOTE:** When ordering, please specify the machine model, weight, and wheelbase.



| Model | Loading capacity per pair           |                                     |
|-------|-------------------------------------|-------------------------------------|
|       | Machine wheelbase<br>100 cm (39 in) | Machine wheelbase<br>150 cm (59 in) |
| 250   | 2500 kg (5511 lbs)                  | 3800 kg (8377 lbs)                  |
| 350   | 2000 kg (4409 lbs)                  | 2500 kg (5511 lbs)                  |
| 400   | 2290 kg (5048 lbs)                  | 2750 kg (6062 lbs)                  |
| 450   | 1070 kg (2359 lbs)                  | 1250 kg (2756 lbs)                  |
| 500   | 2575 kg (5677 lbs)                  | 2945 kg (6493 lbs)                  |

| Model | Length            | Internal Width (A) | External Width (B) | Weight          | Code           |
|-------|-------------------|--------------------|--------------------|-----------------|----------------|
| 250   | 250 cm (98.4 in)  | 34 cm (13.4 in)    | 40 cm (15.7 in)    | 43 kg (95 lbs)  | <b>C890790</b> |
| 350   | 350 cm (138 in)   | 34 cm (13.4 in)    | 40 cm (15.7 in)    | 62 kg (137 lbs) | <b>C890792</b> |
| 400   | 400 cm (157.5 in) | 34 cm (13.4 in)    | 40 cm (15.7 in)    | 56 kg (123 lbs) | <b>C890793</b> |
| 450   | 450 cm (177.2 in) | 34 cm (13.4 in)    | 40 cm (15.7 in)    | 78 kg (172 lbs) | <b>C890794</b> |
| 500   | 500 cm (197 in)   | 34 cm (13.4 in)    | 40 cm (15.7 in)    | 86 kg (190 lbs) | <b>C890795</b> |