


TRENCHER

<http://tiny.cc/trencher>


FEATURES & BENEFITS

- Minimal damage to the ground on trenching area
- Digs from 14 to 20 cm (5.5 to 7.9 in) wide trench and moves all ground to the right side of the trench
- Very fast and clean way to dig trenches for cables, drains, piping etc.

With MultiOne trencher you can easily dig narrow trenches without damaging the ground on the digging area. The trencher does a clean trench which can easily be filled with a bucket or a dozer blade. Planetary drive with hydraulic motor guarantees powerful and trouble free operation. Max digging depths are 60, 90 and 120 cm (23.6, 35.4 and 47.2 in) respectively, depending on model. Digging width is either 14, 16, 18 or 20 cm (5.5, 6.3, 7.1 or 7.9 in), every chain tools kit can be set for different widths. Hard ground version chains have tungsten reinforcements to ensure long lasting performance in hard and rocky soil, otherwise the standard version is the best choice for vegetative ground.

- Trencher is ideal for smaller cable or pipe laying.
- Digging speed with a trencher is 2-3 times quicker compared to a backhoe.
- Combination of an articulated MultiOne and trencher leaves almost no marks of digging operations after the work is done. This makes it a perfect solution for gardens and other lawn areas.

It features an adjustable depth control foot which ensures the operator digs at a set depth at all times and efficient spoil removal for effective compaction back into the trench.

Model	Max Digging Depth	Max Digging Width	Weight	Code
Trencher 60 w/o chain tools ¹	60 cm (23.6 in)	14 to 20 cm (5.5 to 7.9 in)	205,5 kg (453 lbs)	C890206
Trencher 90 w/o chain tools ¹	90 cm (35.4 in)	14 to 20 cm (5.5 to 7.9 in)	235 kg (518 lbs)	C890207
Trencher 120 w/o chain tools ¹	120 cm (47.2 in)	14 to 20 cm (5.5 to 7.9 in)	248 kg (547 lbs)	C890208
Tools	Trencher 60	Trencher 90	Trencher 120	
Tools kit for soft ground ²	C891002	C891003	C891004	
Tools kit for hard ground ²	C891005	C891006	C891007	

(¹) Tools kit required. (²) Trencher required.

Compatibility	1.1	2.3	4.2	5.2	5.3	6.3	7.2	8.4	8.5	11.6	11.9	EZ5	EZ7 EZ8
Model													
60 - soft ground													
90 - soft ground													
120 - soft ground													
60 - hard ground													
90 - hard ground													
120 - hard ground													

Very compatible

Compatible

Not compatible

